

MEDI+RANGE UNDERCOUNTER CABINET WMP135



WMP135

Dimensions (mm)	External	Internal
Width	606	536
Depth	577	434
Height	805	606
Door Opening		606
Capacity		
Capacity cu.ft/ltrs	4.8/135	

KEY FEATURES

- Spark free interior
- Designed and engineered to operate efficiently up to 32°C ambient
- Stainless steel exterior & aluminium interior
- Barrel locked doors
- Magnetic balloon door gaskets with 100% tight seal
- Fitted with white nylon coated, adjustable wire shelves on refrigerator models and static shelves on freezers
- Pilaster racking with removable shelving clips (H models only)
- Precision injected, high density polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)
- Front vented refrigeration system
- Defrost water is vaporised using recycled heat from compressor (H models only)
- High performance helium leak testing
- Air cooled condensing unit

MEDI+ CONTROLLER

- Clear digital display
- Audio and visual hi/lo temp alarm
- Audio and visual door open alarm
- Maximum and minimum temperature memory
- Auto defrost
- Air & evaporator probe
- Lockable keypad
- Condenser cleaning warning to ensure optimum performance is maintained
- Volt free alarm contacts for connecting to supervisory or BMS system
- Modbus network data connection for comprehensive monitoring of temperatures, alarms and defrost via 3rd party supervisory system
- Precise temperature control using decimal point operation

OPTIONS

- Glass door with interior LED lighting (H models only)
- Interior LED lighting for solid door (H models only)
- Punched stainless steel shelves (H models only)
- Additional shelving (H models only)
- Left hand door hang
- Mains failure alarm



MEDI+ RANGE UNDERCOUNTER CABINET WMP135

	HWMP135	LWMP135
Temperature (°C)	+2 / +8°C	-18 / -22°C
Climate Class	Class 4 (30°C)	Class 4 (30°C)
Power Supply	230V/50Hz/1Ph	230V/50Hz/1Ph
Fuse (Amps)	13	13
Defrost	Automatic Off Cycle	Manual
Noise level (dBA)	55	44

Fittings

Shelves	2	2 (fixed)
---------	---	-----------

Electrical / Energy Data

Refrigerant	R600a	R290
Start Up (Amps)	3.7	7.7
Running (Amps)	0.53	1.3
Heat Rejection (Watts)*	194	300

IMPORTANT NOTES:

*Evaporating at -10°C in 32°C Ambient

All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration
Bryggen Road,
North Lynn Industrial Estate
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
Spares: +44(0) 1553 817 017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.co.uk

